LED Multi-pack Lamps

Product Specifications

For an affordable LED upgrade, switch to TCP Multi-Packs, available for dimmable and non-dimmable A-Lamps, BR30s and PAR38s. See how switching to LEDs can maximize savings and minimize maintenance costs.

Reasons to choose LED Multi-Packs from TCP

- Long life: 15,000 hours minimizes replacement and maintenance costs (non-dim A19-10,000 hours)
- Inexpensive alternative for cost-sensitive projects
- ANSI Construction Compliant to fit most applications
- A-Lamps and BR30s are UL approved for damp location when protected from the elements
- PAR38 lamps are UL approved for wet locations

Ideal Applications

- Commercial
- Retail
- Industrial
- Residential

Specifications:

Input Line Voltage	120 VAC
Input Line Frequency	50/60HZ
Lamp Life (Rated)	10,000/15,000 hours
Minimum Starting Temp	-22F/-30C
Maximum Operating Temp	40°C
CRI	80
Warranty	1 year/3 years

c UL us LISTED

1 YEAR WARRANTY * 10,000 HOUR LAMPS

3 YEAR WARRANTY* 15,000 HOUR LAMPS

*Based on 12 hours use per day

TCP®
325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com

LED Multi-pack Lamps

Specifications:

A-Lamps Dimmable

A-Lamps Non-Dimmable

BR30 Dimmable

PAR38 Dimmable

ITEM #	DESCRIPTION	PACK QTY	ENERGY STAR	VOLTAGE	WATTS	LIFE	REPLACEMENT LUMENS	LPW	BEAM ANGLE	CCT	CRI	MOL (inches)	DIA (inches)	BASE	MASTER PACK
A-Lamps Dimmable															
L9A19D1527K4	LED 9W A19 DIM 2700K 4PK	4 PACK	YES	120V	9	15000	60	800	88.9	OMNI	2700	80	4.3	2.4	E26	12
L9A19D1530K4	LED 9W A19 DIM 3000K 4PK	4 PACK	YES	120V	9	15000	60	800	88.9	OMNI	3000	80	4.3	2.4	E26	12
L9A19D1541K4	LED 9W A19 DIM 4100K 4PK	4 PACK	YES	120V	9	15000	60	800	88.9	OMNI	4100	80	4.3	2.4	E26	12
L9A19D1550K4	LED 9W A19 DIM 5000K 4PK	4 PACK	YES	120V	9	15000	60	800	88.9	OMNI	5000	80	4.3	2.4	E26	12
A-Lamps Non Dimmable															
L9A19N1027K4	LED 9.5W A19 ND 2700K 4PK	4 PACK	NO	120V	9.5	10000	60	800	88.9	OMNI	2700	80	4.3	2.4	E26	12
L9A19N1030K4	LED 9.5W A19 ND 3000K 4PK	4 PACK	NO	120V	9.5	10000	60	800	88.9	OMNI	3000	80	4.3	2.4	E26	12
L9A19N1041K4	LED 9.5W A19 ND 4100K 4PK	4 PACK	NO	120V	9.5	10000	60	800	88.9	OMNI	4100	80	4.3	2.4	E26	12
L9A19N1050K4	LED 9.5W A19 ND 5000K 4PK	4 PACK	NO	120V	9.5	10000	60	800	88.9	OMNI	5000	80	4.3	2.4	E26	12
BR30 Dimmable															
L8BR30D1527K2	LED 9W BR30 DIM 2700K 2PK	2 PACK	YES	120V	9	15000	65	650	72.2	110	2700	80	5.2	3.7	E26	12
L8BR30D1530K2	LED 9W BR30 DIM 3000K 2PK	2 PACK	NO	120V	9	15000	65	650	72.2	110	3000	80	5.2	3.7	E26	12
L8BR30D1541K2	LED 9W BR30 DIM 4100K 2PK	2 PACK	NO	120V	9	15000	65	650	72.2	110	4100	80	5.2	3.7	E26	12
L8BR30D1550K2	LED 9W BR30 DIM 5000K 2PK	2 PACK	NO	120V	9	15000	65	650	72.2	110	5000	80	5.2	3.7	E26	12
Par38 Wet Location, Dimmable															
L9OP38D15V30KFL2	LED 13W P38 DIM 30K FL 2PK	2 PACK	NO	120V	13	15000	90	1100	84.6	40	3000	80	5.3	4.8	E26	12
COMING SOON																
L9OP38D15V41KFL2	LED 13W P38 DIM 41K FL 2PK	2 PACK	NO	120V	13	15000	90	1100	84.6	40	4100	80	5.3	4.8	E26	12
L9OP38D15V50KFL2	LED 13W P38 DIM 50K FL 2PK	2 PACK	NO	120V	13	15000	90	1100	84.6	40	5000	80	5.3	4.8	E26	12

c UL us LISTED

1 YEAR WARRANTY * 10,000 HOUR LAMPS

3 YEAR WARRANTY* 15,000 HOUR LAMPS

*Based on 12 hours use per day

TCP®
325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com